

1/32	1/64	0.015625	33/64	0.515625
	3/64	0.03125	17/32	0.53125
	5/64	0.046875	9/16	0.5625
1/16	7/64	0.0625	37/64	0.578125
	9/64	0.078125	19/32	0.59375
3/32	11/64	0.09375	39/64	0.609375
	13/64	0.109375	5/8	0.625
1/8	15/64	0.125	41/64	0.640625
	17/64	0.140625	21/32	0.65625
5/32	19/64	0.15625	43/64	0.671875
	21/64	0.171875		
3/16	23/64	0.1875	11/16	0.6875
	25/64	0.203125	45/64	0.703125
7/32	27/64	0.21875	47/64	0.71875
	29/64	0.234375	3/4	0.75
1/4	31/64	0.25	49/64	0.765625
	33/64	0.265625	25/32	0.78125
9/32	35/64	0.28125	51/64	0.796875
	37/64	0.296875	13/16	0.8125
5/16	39/64	0.3125	53/64	0.828125
	41/64	0.328125		
11/32	43/64	0.34375	27/32	0.84375
	45/64	0.359375	55/64	0.859375
3/8	47/64	0.375	57/64	0.875
	49/64	0.390625	29/32	0.890625
13/32	51/64	0.40625	59/64	0.90625
	53/64	0.421875	15/16	0.921875
7/16	55/64	0.4375	61/64	0.9375
	57/64	0.453125	31/32	0.953125
15/32	59/64	0.46875	63/64	0.96875
	61/64	0.484375	1	1
1/2	63/64	0.5		

### INCHES in DECIMALS of a FOOT

1/16 - 0.0052	1 - 0.0833
3/32 - 0.0078	2 - 0.1667
1/8 - 0.0104	3 - 0.2500
3/16 - 0.0156	4 - 0.3333
1/4 - 0.0208	5 - 0.4167
5/16 - 0.0260	6 - 0.5000
3/8 - 0.0313	7 - 0.5833
1/2 - 0.0417	8 - 0.6667
5/8 - 0.0521	9 - 0.7500
3/4 - 0.0625	10 - 0.8333
7/8 - 0.0729	11 - 0.9167

### Standard Wire Gauges in Approximate Decimals of an Inch and mm.

WIRE GAUGE	AMERICAN or BROWN AND SHARP DIAMETER (inches)	DIAMETER MILLIMETERS	BIRMINGHAM or STUBS	US STANDARD
1	0.2893	7.348	0.300	0.281
2	0.2576	6.544	0.284	0.266
3	0.2294	5.827	0.259	0.250
4	0.2043	5.189	0.238	0.234
5	0.1819	4.621	0.220	0.219
6	0.1620	4.115	0.203	0.203
7	0.1443	3.665	0.180	0.188
8	0.1285	3.264	0.165	0.172
9	0.1144	2.906	0.148	0.156
10	0.1019	2.588	0.134	0.141
11	0.0907	2.304	0.120	0.125
12	0.0808	2.053	0.109	0.109
13	0.0720	1.829	0.095	0.0938
14	0.0641	1.628	0.083	0.0781
15	0.0571	1.450	0.072	0.0703
16	0.0508	1.291	0.065	0.0625
17	0.0453	1.150	0.058	0.0563
18	0.0403	1.024	0.049	0.0500
19	0.0359	0.9116	0.042	0.0438
20	0.0320	0.8118	0.035	0.0375
21	0.0285	0.7230	0.032	0.0344
22	0.0253	0.6438	0.028	0.0313
23	0.0226	0.5733	0.025	0.0281
24	0.0201	0.5106	0.022	0.0250
25	0.0179	0.4547	0.020	0.0219
26	0.0159	0.4049	0.018	0.0188
27	0.0142	0.3606	0.016	0.0172
28	0.0126	0.3211	0.014	0.0156
29	0.0113	0.2859	0.013	0.0141
30	0.0100	0.2546	0.012	0.0125
31	0.0089	0.2268	0.010	0.0109
32	0.0080	0.2019	0.009	0.0102
33	0.00708	0.178	0.008	0.0094
34	0.00630	0.152	0.007	0.0086
35	0.00561	0.138	0.005	0.0078
36	0.00500	0.127	0.004	0.0070
37	0.00445	0.1131		0.0066
38	0.00397	0.1007		0.0063
39	0.00353	0.08969		
40	0.00314	0.07987		

CONDUIT SIZE (I.P.S.)	Approximate No. of Insulated Double Conductor Lengths of Extension					
	Wire - Size Conductor					
	NO. 14	NO. 14 <sup>[1]</sup>	NO. 16	NO. 16 <sup>[2]</sup>	NO. 20	NO. 24
1/2"	1	2	2	1	7	9
3/4"	3	7	4	2	16	21
1"	5	10	6	4	24	29
1 1/4"	7	14	10	5	35	44
1 1/2"	13	23	13	7	48	69
2"	18	48	20	11	73	95

[1] Single Conductor Insulated

[2] Three Conductor Insulated